quadri di allarme

SEMPLICI

FACILITÀ INSTALLAZIONE

SICURI

Quadri per la segnalazione **stati di allarme**

La necessità di monitorare le anomalie viene soddisfatta con i quadri di Allarme Elentek che grazie alle segnalazioni acustiche-visive o tramite GSM gestiscono le anomalie presenti nell'impianto.



UNIT ALARM

UNIT ALARM è un apparecchio applicabile a qualsiasi impianto ove si renda necessario avere delle segnalazioni di allarme anche in assenza di alimentazione di rete.
É disponibile nella versione con allarme sonoro (mod. Unit Alarm 1), con allarme sonoro e visivo lampeggiante (mod. Unit Alarm 2) e nella versione con segnalazione acustica, visiva e GSM (mod. Unit Alarm GSM), ovvero fornita con un kit che comprende antenna e trasmettitore programmabile per la segnalazione dell'attivazione allarme a telefoni cellulari.

CARATTERISTICHE TECNICHE

- **Versione:** monofase 210-250Vac 50/60Hz
- **Controllo stati di allarme**
- **Led a fronte quadro per segnalazione stato funzionamento e allarmi**
- **Pulsanti funzionamento:** TEST - REST - TACITAZIONE
- **Fino a 2 ingressi comando: galleggianti/ pressostati**
- **Segnalazioni:** acustica (90dB) - luminosa (Led) - GSM (sim non inclusa)
- **Impostazione reset allarme in automatico (escludibile)**
- **Timer ritardo disattivazione allarme (programmabile)**
- **Allarmi segnalati:** stato tensione e stato ingressi
- Contatti di uscita allarme generale
- **Autonomia:** 24h in caso di mancanza rete
- **Fusibili di protezioni**
- **Materiale box:** ABS, IP54

Codice	Modello	Lampeggiante	Pressione sonora	Tensione	Autonomia	Box	Materiale	Peso
01500	UNIT ALARM 1	-	90 dB	12 Vdc	24h	P1	Plastico	1 Kg
01501	UNIT ALARM 2	Rosso	90 dB	12 Vdc	24h	P1	Plastico	1 Kg
01502	UNIT ALARM GSM	Rosso	90 dB	12 Vdc	24h	P2	Plastico	1,5 Kg

Quadri applicabili a qualsiasi impianto ove si renda necessario avere delle segnalazioni di allarme anche in assenza di alimentazione di rete, abbinabili ai nostri quadri elettrici: semplici, compatti ed economici. Disponibili nella versione con allarme sonoro, con allarme sonoro e visivo lampeggiante e nella versione con segnalazione acustica, visiva e GSM.



FLASH


Dispositivo elettrico di **allarme acustico** e visivo da abbinare ai nostri quadri elettrici: semplice, compatto ed economico.

CARATTERISTICHE TECNICHE


- **Alimentazione:** 230/24 Vac
- **Lampeggiante:** rosso
- **Allarme sonoro:** 90 dB
- 1 ingresso normalmente aperto per comando allarme da contatti puliti
- 1 Ingresso normalmente chiuso per comando allarme da contatti puliti
- **Materiale box:** ABS, IP54

Codice	Modello	Alimentazione	Pressione sonora	Tensione	Box	Materiale	Peso
01503	FLASH 24	24V	90 dB	24 Vdc	P1	Plastico	1Kg
01505	FLASH 230	12V	90 dB	230 Vdc	P1	Plastico	1Kg

DIMENSIONI



P1



P2

alarm panels

SIMPLE

EASE OF INSTALLATION

SAFE

Panels for **alarm state indication**

Products applicable to any system where alarm indications are required even in the absence of network power supply.



UNIT ALARM

UNIT ALARM is a device applicable to any system where alarm signaling is needed, even in the absence of network power supply. It is available in the version with a sound alarm (model Unit Alarm 1), with both sound and flashing visual alarm (model Unit Alarm 2), and in the version with acoustic, visual, and GSM signaling (model Unit Alarm GSM), which comes with a kit including an antenna and a programmable transmitter for sending alarm activation notifications to mobile phones.

TECHNICAL SPECIFICATIONS

- **Version:** single-phase 210-250Vac 50/60Hz
- **Alarm status monitoring**
- **LED on the front of the panel for operation status and alarm signaling**
- **Operation buttons:** TEST - RESET - SILENCING
- **Up to 2 command inputs:** float switches/pressure switches
- **Signaling:** acoustic (90dB) - visual (LED) - GSM (SIM not included)
- **Automatic alarm reset setting (optional)**
- **Programmable alarm deactivation delay timer**
- **Reported alarms:** voltage status and input status
- **General alarm output contacts**
- **Autonomy:** 24h in case of power failure
- **Protection fuses**
- **Enclosure material:** ABS, IP54

Code	Model	Flashing light	Sound pressure	Voltage	Autonomy	Box	Material	W
01500	UNIT ALARM 1	-	90 dB	12 Vdc	24h	P1	Plastic	1 Kg
01501	UNIT ALARM 2	Red	90 dB	12 Vdc	24h	P1	Plastic	1 Kg
01502	UNIT ALARM GSM	Red	90 dB	12 Vdc	24h	P2	Plastic	1,5 Kg

Panels applicable to any system where it is necessary to have alarm signals even in the absence of mains power, combinable with our electrical panels: simple, compact and economical. Available in the version with audible alarm, with audible and visual flashing alarm and in the version with acoustic, visual and GSM signaling.



FLASH


Electrical device for **acoustic and visual alarm** to be paired with our electrical panels: simple, compact, and economical.

TECHNICAL SPECIFICATIONS


- **Power supply:** 230/24 Vac
- **Flashing light:** red
- **Sound alarm:** 90 dB
- 1 normally open input for alarm command from clean contacts
- 1 normally closed input for alarm command from clean contacts
- **Enclosure material:** ABS, IP54

Code	Model	Power	Sound pressure	Voltage	Box	Material	W
01503	FLASH 24	24V	90 dB	24 Vdc	P1	Plastic	1Kg
01505	FLASH 230	12V	90 dB	230 Vdc	P1	Plastic	1Kg

DIMENSIONS



P1



P2