

Model	lt.	Type	l/min	m³/h	c.f.m.	kW	hp	Volt	Amp.	r.p.m.	n°	stage n°	bar	p.s.i.	kg	L x B x H			Guaranteed
																			LwA
CH 25/110	25	CH110	115	6,9	4,1	0,75	1	230	4,7	1400	1	1	8	116	28	678	340	635	95
CH 25/210	25	CH210	220	13,2	7,6	1,5	2	230	8,2	2800	1	1	8	116	29	678	340	635	95
CH 50/210	50	CH210	220	13,2	7,6	1,5	2	230	8,2	2800	1	1	8	116	38	1030	450	832	95

Compressori carrellati monocilindrici
Compressori carrellati completi di maniglia e di ruote, per un facile spostamento. Funzionamento automatico comandato da pressostato e valvola di ritegno. Dotati di strumenti di controllo: manometri, valvola di sicurezza, riduttore di pressione con rubinetto portagomma e valvola scarico condensa.

Wheel mounted single cylinder compressors
Wheel mounted compressors provided with handle and wheels easy to be transported. Automatic operation controlled by a pressure switch and a non return valve. The control device include: pressure gauges, safety valve, pressure reducing valve with hose holder cock and condense drain valve.

© Speroni S.p.A., Castelnovo di Sotto (Reggio Emilia), 2022