# CR 200-3 PL

airmec AIR COMPRESSOR

## Compressori monostadio a cinghia
Single-stage belt driven compressors

**MADE IN ITALY**




| | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | AIR AIR | | | | 1' | | | | | | H B L | | | dBA Guaranteed |
| Model | lt. | Type | l/min | kW | Hp | Volt | r.p.m. | n° | stage n° | bar | p.s.i. | kg | L | B | H | LwA |
| **CRM 200-3 PL** | 200 | TH 25 | 320 | 2,2 | 3 | 230 | 1025 | 2 | 1 | 10 | 145 | 94 | 1460 | 500 | 900 | 95 |
| **CRT 200-3 PL** | 200 | TH 25 | 320 | 2,2 | 3 | 400 | 1025 | 2 | 1 | 10 | 145 | 94 | 1460 | 500 | 900 | 95 |

**Compressori monostadio a cinghia**
Testata bicilindrica in ghisa con valvole in acciaio inox. Il motore elettrico monofase è sovradimensionato con forte coppia di avviamento completo di protezione termica a riarmo manuale.
Il motore elettrico trifase è protetto da un interruttore magnetotermico, montato sul pressostato.

***Single-stage belt driven compressors***
*Two-cylinders cast iron head provided with stainless steel valves.*
*The single-phase electric motor is oversized with high starting torque complete with thermal protection at manual reset.*
*The three-phase electric motor is protected by an overload switch, mounted on the pressure switch.*

© Speroni S.p.A. | Castelnovo di Sotto (Reggio Emilia) 2026