# CR 303 - 304 - 305 - 307




| Model | lt. | Type | l/min | m³/h | c.f.m. | kW | hp | Volt | Amp. | r.p.m. | n° | stage n° | bar | p.s.i. | kg | L x B x H | | | Guaranteed |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | | | | | | | | | | | | | | | | | | LwA |
| **CRM 303** | 270 | K18 | 385 | 23,1 | 13,6 | 2,2 | 3 | 230 | 12 | 850 | 2 | 1 | 10 | 145 | 146 | 1675 | 720 | 1200 | 95 |
| **CR 303** | 270 | K18 | 385 | 23,1 | 13,6 | 2,2 | 3 | 230 400 | 5 | 850 | 2 | 1 | 10 | 145 | 147 | 1675 | 720 | 1200 | 95 |
| **CR 304** | 270 | K28 | 460 | 27,6 | 16,3 | 3 | 4 | 230 400 | 6,7 | 900 | 2 | 2 | 10 | 145 | 159 | 1675 | 720 | 1200 | 97 |
| **CR 305** | 270 | K30 | 727 | 43,26 | 25,7 | 4 | 5,5 | 230 400 | 8,6 | 850 | 2 | 2 | 10 | 145 | 178 | 1675 | 720 | 1200 | 97 |
| **CR 307** | 270 | K30 | 800 | 48 | 26,25 | 5,5 | 7,5 | 230 400 | 11 | 1100 | 2 | 2 | 10 | 145 | 188 | 1675 | 720 | 1200 | 97 |

### Compressori doppio stadio a cinghia

Testata bicilindrica e piastra portavalvole in ghisa, valvole lamellari in acciaio inox ad elevata resistenza. Il funzionamento a basso regime di giri ed un volano sovradimensionato garantiscono un esercizio a bassa temperatura.
Un ulteriore raffreddamento è garantito da collettori intermedi e finali con ampie alettature.
Il motore elettrico trifase è comandato da un teleruttore con protezione magnetotermica.

### *Two-stage belt driven compressors*

*Two-cylinders cast iron head provided with cast iron valve plate and stainless steel valves at high resistance. The functioning at low r.p.m. and oversized fly wheel permit a low working temperature. Intermediate and ending collectors with ample fins allow a further cooling. The three-phase electric motor is controlled by a contactor with thermic protection.*


© Speroni S.p.A., Castelnovo di Sotto (Reggio Emilia), 2022