
DOSING PUMP

TEKNA TCK Series – Solenoid Dosing Pump

TECHNICAL CHARACTERISTICS



- Flow rates: from 2.5 to 110 l/h
- Max back pressure: up to 20 bar
- Power supply: 100÷240V 50/60 Hz
- Stroke rate: from 120 to 300 strokes/minute
- Pump head: PVDF
- Diaphragm: PTFE
- External Enclosure: PP reinforced with fiber glass protection degree IP65
- Manually priming valve
- Installation kit: Included

Seko Tekna TCK Series is a digital dosing pump with:

- Constant flow rate
- Timed dosing with a weekly programmable timer
- Programmable timed relay by activating a dry contact

Also TCK series with only 4 sizes, is possible to cover the same range of performances, with a flow rate range from 2.5 to 110 l/h and a back pressure from 0.1 to 20 bar. The power supply is 100÷240 Vac – 50/60 Hz, therefore the same pump can operate with different supply voltage. The standard pump head is in PVDF, therefore high chemical compatibility with several liquids end but is available in PVC as well, on request.
Tekna TCK series is equipped with a manually priming pump for the start up.
The pump is furnished with a complete standard installation kit, which includes: PVDF foot filter and injection valve, PVC suction tube, PE delivery tube. Moreover is available an installation kit in PVDF-T, on request.
The ambient temperature at the site of pump installation cannot exceed 40°C, and the relative humidity cannot be above 90%; the pump cannot be installed in a place exposed to sun or bad weather.

Technical data can be changed without notice.

DOSING PUMP

TEKNA TCK Series – Solenoid Dosing Pump

KEY CODE

model

TCK — Constant flow rate manually adjustable. Timed dosing with a weekly programmable timer, programmable timed relay by activating a dry contact

hydraulics	Pressure [bar]	Flow rate [l/h]	Capacity [cc/stroke]	Frequency [stroke/1']	Ø Connections IN / EXT [mm]
600	20	2,5	0,35	120	4 / 7 discharge 4 / 6 suction
	18	3	0,42		
	14	4,2	0,58		
	8	7	0,97		
603	12	4	0,42	160	4 / 6
	10	5	0,52		
	8	6	0,63		
	2	8	0,83		
800	16	7	0,38	300	4 / 6
	10	10	0,55		
	5	15	0,83		
	1	18	1,00		
803	5	20	1,11	300	8 / 12
	4	32	1,78		
	2	62	3,44		
	0,1	110	6,11		

power supply

N	100÷240 Vac 50/60 Hz

liquid end

H	PVDF	
A	PVDF - automatic degassing	*NOT for 803 hydraulic*
I	SS316L	

installation kit

H	PVDF	
P	PVDF-T	
X	with 1,5 bar injection valve	
0	WITHOUT kit	*only for SS316L liquid end*

seals

0	FKM-B	
1	EPDM	
2	PTFE	
3	FFKM	*NOT for 803 hydraulic - kit with PTFE seals*

optional

0	standard

optional / customization

00	standard

TPG	800	N	H	H	0	0	M0

Technical data can be changed without notice.

DOSING PUMP

TEKNA TCK Series – Solenoid Dosing Pump


HYDRAULIC CHARACTERISTICS

Pump model	Pressure [bar]	Flow Rate [l/h]	Frequency max [stroke/min]	*Stroke capacity [cc/stroke]*	*Connection [mm]*		Power supply	Consumption [W]	
					Suction	Discharge		Min	Max
TCK600N	20 18 14 8	2,5 3,0 4,2 7,0	120	0,35 0,42 0,58 0,97	*4/6*	*4/7*	100÷240 Vac	14,0	20,0
TCK603N	12 10 8 2	4,0 5,0 6,0 8,0	160	0,42 0,52 0,63 0,83	4/6	4/6	100÷240 Vac	15,0	22,0
TCK800N	16 10 5 1	7,0 10,0 15,0 18,0	300	0,39 0,56 0,83 1,00	4/6	4/6	100÷240 Vac	22,0	36,0
TCK803N	5 4 2 0	20,0 32,0 62,0 110,0	300	1,11 1,78 3,44 6,11	8/12	8/12	100÷240 Vac	-	-


**** Pressure Data in the table refer to the measured parameters on the plant, including the use of SEKO STANDARD injection fitting.***


DIMENSIONS

500 – 600 – 603 - 800



803






INSTALLATION KIT	PVDF	PVDF-T
foot filter	●	●
injection valve	●	●
PVC suction tube (4 m)	●	
PE delivery tube (2 m)	●	
Wall and base fixing bracket	●	


Technical data can be changed without notice.

DOSING PUMP

TEKNA TCK Series – Solenoid Dosing Pump

PERFORMANCE





Technical data can be changed without notice.